

Next Generation Radioisotope Identification Device



Detection and Identification: Fast, Accurate and Easy



RADEAGLE is a state-of-the-art handheld, radioisotope identification device (RIID) delivering superior speed and accuracy.

- Combining a large, high sensitivity crystal with an intelligent algorithm, the RADEAGLE can **quickly, accurately, and simultaneously detect and identify** four or more isotopes, typically in under 30 seconds, even in complex shielded or masked scenarios.
- **ANSI 42.34 compliant**, the RADEAGLE offers a **user-friendly interface** that is intuitive, simple to navigate, provides visually clarity, and utilizes an extensive array of alarms.
- Supports a **variety of scintillation crystals** including Nal(TI), CeBr3 and LaBr3(Ce) to optimize performance across multiple applications.
- Incorporating **decades of industry expertise** in detection and identification algorithms along with advanced hardware, electrical, and software systems, the **RADEAGLE is the handheld RIID of choice**.

Key Customers and Applications

- ✓ First Responders and Emergency Management
- ✓ Customs and Border Protection
- ✓ Security and Military Forces
- ✓ Nuclear Safeguards
- ✓ Environmental Management and Cleanup
- ✓ Nuclear Medicine and Scientific Institutes
- ✓ Scrap Steel and Recycling

Intelligent Algorithm – Unparalleled Speed and Accuracy

The RADEAGLE algorithm is unique, using a neuron ensemble to create a multi-agent system. This multi-agent system in turn uses a mimetic learning algorithm that adapts reference data to the unique signature of the detector's sensors. While continuously measuring background radiation, this "neuro-spectroscopic brain," delivers unparalleled speed and accuracy for detecting and identifying over 100 nuclides, exceeding ANSI 42.34 requirements.



Operating Modes

The RADEAGLE uses five basic operating modes: Dose Rate, Detect, Easy-ID, Spectrum, and Advanced. These **five simple modes gives the user full system control** ranging from quick and accurate identification to extensive spectrum analysis to expert system configurations.



Application Centric Approach

A key benefit of the RADEAGLE algorithm is its optimization for multiple real-world applications. Through extensive simulation, validated and refined with real world empirical testing, the RADEAGLE's performance is tuned and optimized for key isotopes associated with SNM in the nuclear security and safeguards market, NORM and IND for environmental and industrial applications and MED for nuclear medicine. Underwater measurements are also supported with a submersible, Nal model.

Common Technical Specifications

RADIOLOGICAL PERFORMANCE					
Energy Range/MCA	11 keV to 3 MeV / 2048 channels				
Calibration Source	Natural background. Optional embedded calibration source.				
	Default Isotopes: ^{110m} Ag, ²⁴¹ Am, ¹³³ Ba, ²⁰⁷ Bi, ¹⁰⁹ Cd, ²⁵² Cf (requires neutron detection), ⁵⁷ Co, ⁶⁰ Co, ⁵¹ Cr, ¹³⁴ Cs, ¹³⁷ Cs, ¹⁵² Eu, ⁶⁸ Ga, ¹²³ I, ¹²⁵ I, ¹³¹ I, ¹¹¹ In, ⁴⁰ K, ⁵⁴ Mn, ⁹⁹ Mo2, ²² Na, ²³⁷ Np, ²³⁸ Pu, ²³⁹ Pu, ⁽²⁴⁰ Pu, ²⁴¹ Pu as part of compositions) ²²⁶ Ra, ⁷⁵ Se, ^{99m} Tc, ²³² Th, ²⁰¹ Tl, ²³³ U, ²³⁵ U, ²³⁸ U				
Nuclide Library	Optional Isotopes (contact factory): ^{109m} Ag, ¹⁹⁸ Au, ^{135m} Ba, ¹⁴⁰ Ba, ²¹³ Bi, ¹¹⁶ Cd, ⁵⁸ Co, ¹³⁹ Ce, ¹⁴¹ Ce, ¹⁴⁴ Ce, ¹³¹ Cs, ⁶⁴ Cu, ⁶⁷ Cu, ¹⁶⁵ Dy, ¹⁸ F, ⁵⁹ Fe, ⁶⁷ Ga, ⁶⁸ Ge, ^{166m} Ho, ¹²⁴ I, ¹³² I, ¹³³ I, ¹⁹⁴ Ir, ⁴² K, ^{81m} Kr, ¹³⁸ La, ¹⁴⁰ La, ¹⁷³ Lu, ¹⁷⁴ Lu, ¹⁷⁶ Lu, ¹⁷⁷ Lu, ⁵⁶ Mn, ²⁴ Na, ⁹⁵ Nb, ⁹⁶ Nb, ¹⁴⁷ Nd, ²¹² Pb, ¹⁰³ Pd, ¹⁴⁴ Pr, ⁸² Rb, ¹⁶⁶ Re, ¹⁸⁸ Re, ¹⁰⁶ Rh, ¹⁰³ Ru, ¹⁰⁶ Ru, ¹⁵³ Sm, ¹¹³ Sn, ⁸² Sr, ⁸⁹ Sr, ⁹⁰ Sr, ¹³² Te, ²²⁸ Th, ⁴⁴ Ti, ²⁰² TI, ²⁰⁴ TI, ²³² U, ²³⁷ U, ¹⁸⁷ W, ^{131m} Xe, ¹³³ Xe, ^{133m} Xe, ¹³⁵ Xe, ⁸⁸ Y, ⁹⁰ Y, ¹⁶⁹ Yb, ¹⁷⁷ Yb, ⁶⁵ Zn, ⁹⁵ Zr				
Nuclide Categories	Special nuclear material (SNM), Naturally occurring radiation (NORM), Industrial emitter (IND), or Medical source (MED)				
PHYSICAL					
Dimensions	248 mm x 115 mm x 152 mm (9.8" x 4.5" x 6.0")				
Display	640 x 480, 89 mm (3.5") Transflective Color TFT				
Batteries	Rechargeable AA NiMH battery pack, auxiliary battery case for AA NiMH or alkaline				
Operational Run Time	>8 hours with standard battery pack				
ENVIRONMENTAL					
Operating Temperature	-20 °C to +50 °C (-4 °F to +122 °F)				
Relative Humidity	10% – 90%, non-condensing				
Protection Rating	IP65, (3SGA models are IP68)				
COMPUTATIONAL					
Memory	>16 GB (1,000,000 spectra)				
CPU Speed	1 GHz				
File Formats	ANSI N42.42, SPE (IAEA)				
Connectivity	USB, WiFi, GPS (optional)				
SOFTWARE					
Operating System	Microsoft Windows (XP, Vista, 7, 8, 10), MAC OS X Yosemite, Linux (tested for Ubuntu)				

Model Specific Technical Specifications

Mode!*	Detector Type	Detector Dimensions	РМТ	GM	He ^{3**}	Resolution @ 662 keV ¹³⁷ Cs at ambient room temp	Sensitivity cps/µSv/h @ 662 keV ¹³⁷ Cs	Dose Rate Range Detector µSv/h	Dose Rate Range GM, up to Sv/h	Weight (grams)
RADEAGLE-3SG	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~		≤7.2%	>2500	0.01–200	1	~2620
RADEAGLE-3SG-H	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~	✓	≤7.2%	>2500	0.01–200	1	~2720
RADEAGLE-3SGA	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~		≤7.2%	>2500	0.01–200	1	~2620
RADEAGLE-3SGA-H	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~	✓	≤7.2%	>2500	0.01–200	1	~2720
RADEAGLE-2CG	CeBr3	50.8x25.4 mm (2x1 in)	3"	~		≤4.0%	>1600	0.01–300	1	~2200
RADEAGLE-2CG-H	CeBr3	50.8x25.4 mm (2x1 in)	3"	~	✓	≤4.0%	>1600	0.01–300	1	~2620
RADEAGLE-3CG	CeBr3	76.2x20.3 mm(3x0.8 in)	3"	~		≤4.0%	>2500	0.01–200	1	~2620
RADEAGLE-3CG-H	CeBr3	76.2x20.3 mm(3x0.8 in)	3"	~	✓	≤4.0%	>2500	0.01–200	1	~2720
RADEAGLE-2LG	LaBr3(Ce)	50.8x25.4 mm (2x1 in)	3"	~		≤3.0%	>1600	0.01–300	1	~2250
RADEAGLE-2LG-H	LaBr3(Ce)	50.8x25.4 mm (2x1 in)	3"	~	~	≤3.0%	>1600	0.01–300	1	~2550

*see ordering information for GPS models **with internal moderator



RADEAGLE AQUA

- IP 68
- Submersible to 15 meters
- Tested and proven ID algorithm with special modification to compensate for attenuation and scatter in water
- Floats in the water
- Rugged and durable for military use
- Bright yellow color for easy location in water
- Ideal for use in maritime environments immune to salt spray





It Floats!



Ordering Information (All models include carrying case and accessories)

Model	Description
RADEAGLE-3SG	Gamma Handheld RIID with 3x1 Nal(TI) detector and GM tube.
RADEAGLE-3SG-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube and embedded calibration source.
RADEAGLE-3SG-GPS	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube and GPS.
RADEAGLE-3SG-GPS-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, GPS and embedded calibration source.
RADEAGLE-3SG-H	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, and He-3 detector.
RADEAGLE-3SG-H-ES	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, He-3 detector and embedded calibration source.
RADEAGLE-3SG-H-GPS	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, He-3 detector and GPS.
RADEAGLE-3SG-H-GPS-ES	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, He-3 detector GPS and embedded calibration source.
RADEAGLE-3SGA	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube and AQUA option.
RADEAGLE-3SGA-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option and embedded calibration source.
RADEAGLE-3SGA-GPS	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option and GPS.
RADEAGLE-3SGA-GPS-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option, GPS and embedded calibration source.
RADEAGLE-3SGA-H	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option and He-3 detector.
RADEAGLE-3SGA-H-ES	Gamma/Neutron Handheld RIID with 3x1 NaI(TI) detector, GM tube, AQUA option, He-3 detector and embedded calibration source.
RADEAGLE-3SGA-H-GPS	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option, He-3 detector, and GPS.
RADEAGLE-3SGA-H-GPS-ES	Gamma/Neutron Handheld RIID with 3x1 NaI(TI) detector, GM tube, AQUA option, He-3 detector, GPS and embedded calibration source.
RADEAGLE-2CG	Gamma Handheld RIID with 2x1 CeBr3 detector and GM tube.
RADEAGLE-2CG-ES	Gamma Handheld RIID with 2x1 CeBr3 detector, GM tube and embedded calibration source.
RADEAGLE-2CG-GPS	Gamma Handheld RIID with 2x1 CeBr3 detector, GM tube and GPS.
RADEAGLE-2CG-GPS-ES	Gamma Handheld RIID with 2x1 CeBr3 detector, GM tube, GPS and embedded calibration source.
RADEAGLE-2CG-H	Gamma/Neutron Handheld RIID with 2x1 CeBr3 detector, GM tube and He-3 detector.
RADEAGLE-2CG-H-ES	Gamma/Neutron Handheld RIID with 2x1 CeBr3 detector, GM tube, He-3 detector and embedded calibration source.
RADEAGLE-2CG-H-GPS	Gamma/Neutron Handheld RIID with 2x1 CeBr3 detector, GM tube, He-3 detector and GPS.
RADEAGLE-2CG-H-GPS-ES	Gamma/Neutron Handheld RIID with 2x1 CeBr3 detector, GM tube, He-3 detector, GPS and embedded calibration source.
RADEAGLE-3CG	Gamma Handheld RIID with 3x0.8 CeBr3 detector and GM tube.
RADEAGLE-3CG-ES	Gamma Handheld RIID with 3x0.8 CeBr3 detector, GM tube and embedded calibration source.
RADEAGLE-3CG-GPS	Gamma Handheld RIID with 3x0.8 CeBr3 detector, GM tube and GPS.
RADEAGLE-3CG-GPS-ES	Gamma Handheld RIID with 3x0.8 CeBr3 detector, GM tube, GPS and embedded calibration source.
RADEAGLE-3CG-H	Gamma/Neutron Handheld RIID with 3x0.8 CeBr3 detector, GM tube and He-3 detector.
RADEAGLE-3CG-H-ES	Gamma/Neutron Handheld RIID with 3x0.8 CeBr3 detector, GM tube, He-3 detector and embedded calibration source.
RADEAGLE-3CG-H-GPS	Gamma/Neutron Handheld RIID with 3x0.8 CeBr3 detector, GM tube, He-3 detector and GPS.
RADEAGLE-3CG-H-GPS-ES	Gamma/Neutron Handheld RIID with 3x0.8 CeBr3 detector, GM tube, He-3 detector, GPS and embedded calibration source.

Ordering Information – continued

Model	Description			
RADEAGLE-2LG	Gamma Handheld RIID with 2x1 LaBr3(Ce) detector and GM tube.			
RADEAGLE-2LG-ES	Gamma Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube and embedded calibration source.			
RADEAGLE-2LG-GPS	Gamma Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube and GPS.			
RADEAGLE-2LG-GPS-ES	Gamma Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube, GPS and embedded calibration source.			
RADEAGLE-2LG-H	Gamma/Neutron Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube and He-3 detector.			
RADEAGLE-2LG-H-ES	Gamma/Neutron Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube, He-3 detector and embedded calibration source.			
RADEAGLE-2LG-H-GPS	Gamma/Neutron Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube, He-3 detector and GPS.			
RADEAGLE-2LG-H-GPS-ES	Gamma/Neutron Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube, He-3 detector, GPS and embedded calibration source.			
Accessories				
RE-AP009-1	Accu-Pack Battery Charger with battery (spare)			
RE-AP009-2	Accu-Pack Battery Charger only.			
RE-CA019	Auto Power Adapter, 12 V			
RE-CC022	Carrying Case			
RE-CM020	Charger Module			
RE-HB021	Carrying Holster with Strap			

Specifications subject to change 061019



www.ortec-online.com

Tel. (865) 482-4411 • Fax (865) 483-0396 • ortec.info@ametek.com 801 South Illinois Ave., Oak Ridge, TN 37830 U.S.A. For International Office Locations, Visit Our Website

